

SPECIFICATIONS

Carrying weight 465 lb 211 kg
Maximum Payload 750 lb 340 kg
Camera Mount Height 5 ft. 1.52 m
Camera mount Height with 12" Riser 6 ft. 1.83 m
Minimum Camera Mount Height 18 in. 46 cm
Minimum Camera Mount Height with 12" Riser 2 ft. 6 3/4 in. 78 cm
Minimum Camera Mount Height with 90° Drop Down 2 in. 5 cm
Vertical Travel 3 ft. 6 in. 1.07 m
*Maximum payload with accumulator charge at 3,300 psi 750 lb. 340 kg
**Maximum payload with high post kit 1,500 lbs. 680 kg
Maximum boom lifts (fully charged at 3,300 psi) 6 lifts
Chassis length 2 ft. 3 1/2 in. 70 cm
Chassis width 4 ft. 3 in. 1.29 m
Steering Post height 3 ft. 4 3/4 in. 1.03 m
Front deck height 12 3/4 in. 32 cm
Rear deck height 17 in. 43 cm
Minimum deck height for traveling 19 1/2 in. 50 cm
Minimum turn radius (round mode) 2 ft. 4 in. 71 cm
Minimum turn radius (conventional mode) 3 ft. 10 in. 1.17 m
Accumulator charging time (110 AC and DC) under 60 sec
Accumulator charging time (hand pump) 2 minutes
*Standard operational weight (without payload) 465 lb 211 kg
Hustler w/ high post kit operational weight (w/o payload) 505 lb 229 kg
Dolly Shipping Weight w/Crate 765 lb 347.7 kg
Dolly Crate Shipping Dimensions L 61 in. x W 38 in. x H 32 in.
Dolly Accessory Cart Shipping Weight w/Crate 810 lb. 367.4 kg
Dolly Accessory Cart Crate Shipping Dimensions
L 63 in. x W 38 in. x H 53 in.
*Payload includes All Items
(i.e. Man, Camera, Platform, Turret, Crane Arm, etc.) on Arm
**Payload includes All Items
(i.e. Man, Camera, Platform, Turret, Crane Arm, etc.) on Base Mount.

Accessories:

Rear Deck Board
Hustler IV Medium Tire Set
4 Way Leveling/Swing Head
Tracking Bar Extensions
Lower and Upper Front boards
Standing Board
Side boards
Filler Boards
Side Board Seat Adapters
Seat-locking swivel
Seat, 12" seat risers
90 deg low plate
3" camera riser
6" camera riser
12" camera riser
16" camera offset
24" camera offset
push/lift bars
Accessory Cart
Nose Seat
CB Nose plate & seat pocket
Enterprise low mode with footrest