## TECHNOLOGY FOR FILM, TELEVISION, THEATRE AND EVENTS

## SPECIFICATIONS

Maximum camera mount height (position 1 - 90° mode)4 ft. 11 3/4 in.1.Minimum camera mount height (position 1 - 90° mode)29 1/2 in.7Vertical boom travel (position 1 - 90° mode)30 1/4 in.7Maximum camera mount height (position 2 - 45° mode)4 ft. 9 1/2 in.1Minimum camera mount height (position 2 - 45° mode)25 1/2 in.6Vertical boom travel (position 2 - 45° mode)32 in.8	113 kg 1.51 m 74.93 cm 77 cm 1.46 m 65 cm 81 cm 1.28 m
Minimum camera mount height (position 1 - 90° mode)   29 1/2 in.   7     Vertical boom travel (position 1 - 90° mode)   30 1/4 in.   7     Maximum camera mount height (position 2 - 45° mode)   4 ft. 9 1/2 in.   1     Minimum camera mount height (position 2 - 45° mode)   25 1/2 in.   6     Vertical boom travel (position 2 - 45° mode)   32 in.   8	74.93 cm 77 cm 1.46 m 65 cm 81 cm 1.28 m
Vertical boom travel (position 1 - 90° mode)   30 1/4 in.   7     Maximum camera mount height (position 2 - 45° mode)   4 ft. 9 1/2 in.   1.     Minimum camera mount height (position 2 - 45° mode)   25 1/2 in.   6     Vertical boom travel (position 2 - 45° mode)   32 in.   8	77 cm 1.46 m 65 cm 81 cm 1.28 m
Maximum camera mount height (position 2 - 45° mode)   4 ft. 9 1/2 in.   1.     Minimum camera mount height (position 2 - 45° mode)   25 1/2 in.   6     Vertical boom travel (position 2 - 45° mode)   32 in.   8	1.46 m 65 cm 81 cm 1.28 m
Minimum camera mount height (position 2 - 45° mode)   25 1/2 in.   6     Vertical boom travel (position 2 - 45° mode)   32 in.   8	65 cm 81 cm 1.28 m
Vertical boom travel (position 2 - 45° mode) 32 in. 8	81 cm 1.28 m
	1.28 m
Maximum camera mount height (position 3 - low mode)   4 ft. 2 1/2 in.   1.	
	10
Minimum camera mount height (position 3 - low mode) 19 1/4 in. 4	48 cm
Vertical boom travel (position 3 - low mode) 31 /4 in. 7	79 cm
Maximum camera mount height (position 4 - extender mode)   4 ft. 11 in.   1.	1.49 m
Minimum camera mount height (position 4 - extender mode)   20 3/4 in.   5	53 cm
Vertical boom travel (position 4 - extender mode)     38 1/4 in.     9	97 cm
Minimum camera mt height (low bar/lowest 4-way leveling head) 5 in.	12 cm
Maximum camera mt height (low bar/lowest 4-way leveling head)   36 in   9	91 cm
Maximum payload with high post kit 1,100 lb 4	499 kg
Maximum Boom Lifts (fully charged) 4 Lifts	
Chassis Maximum Length (wheels fully extended) 43 in. 1.	1.09 m
Chassis Minimum Length (wheels fully retracted) 34 1/2 in. 8	88 cm
Minimum chassis height for transportation 43 in.	1.09 m
Chassis width - legs at 0° position 34 1/2 in. 8	88 cm
Chassis width - legs at 17° position 16 in. 4	41 cm
Chassis width - legs at 45° position 20 in. 5	51 cm
Chassis width - legs at 90° position 32 in. 8	81 cm
Steering post height 35 in. 8	89 cm
Minimum turn radius 24 in. 6	61 cm
Minimum door width PeeWee can be carried through   16 in.   4	41 cm
Accumulator charging time (empty to full) 60 sec.	
Operational weight 329 lb 14	149 kg
Operational Weight w/ High Post Kit (no payload) 386 lb 17	175 kg
Dolly Shipping Weight w/Crate 475 lb 2	215.4 kg
Dolly Shipping Crate Dimensions   L 43 in. x W 27 in. x H 36 in.	
Dolly Accessory Cart Shipping Weight w/Crate 346 lb 15	156.9 kg
Dolly Accessory Cart Crate Shipping Dimensions L 44 in. x W 35 in. x H 28 in.	
*Payload includes All Items (i.e. Man, Camera, Platform, Turret, Crane Arm, etc.) on Arm	
**Payload includes All Items (i.e. Man, Camera, Platform, Turret, Crane Arm, etc.) on Base Mount.	

## Accessories:

4-way leveling head Med Tire set Front board Narrow sideboards Dolly seats 12" seat risers (long post) 12" camera riser 24" camera offset low shot bracket Accessory cart