

**SPECIFICATIONS**

|  |                                |          |
|--|--------------------------------|----------|
| Carrying Weight  | 295 lb                         | 134 kg   |
| *Maximum Payload with accumulator charge at 2,400 psi  | 320 lb                         | 145 kg   |
| *Maximum Payload with accumulator charge at 2,600 psi  | 350 lb                         | 159 kg   |
| Maximum Camera Mount Height (Position 1- 90 degrees Mode)  | 5 ft. 0.5 in.                  | 1.53 m   |
| Minimum Camera Mount Height (Position 1- 90 degrees Mode)  | 27.25 in                       | 69 cm    |
| Vertical Boom Travel (Position 1- 90 degrees Mode)   | 33.25 in                       | 84 cm    |
| Maximum Camera Mount Height (Position 2 - 45 degrees Mode)                                       | 4 ft. 10.5 in.                 | 1.48 m   |
| Minimum Camera Mount Height (Position 2 - 45 degrees Mode)                                       | 26 in                          | 66 cm    |
| Vertical Boom Travel (Position 2 - 45 degrees Mode)  | 33.25 in                       | 84 cm    |
| Maximum Camera Mount Height (Position 3 - Low Mode)  | 4 ft. 3.5 in.                  | 1.3 m    |
| Minimum Camera Mount Height (Position 3 - Low Mode)  | 19 in                          | 48 cm    |
| Vertical Boom Travel (Position 3 - Low Mode)   | 33.25 in                       | 84 cm    |
| Maximum Camera Mount Height (Position 4 - Extender Mode)   | 5 ft. 0.5 in.                  | 1.53 m   |
| Minimum Camera Mount Height (Position 4 - Extender Mode)   | 19 in                          | 48 cm    |
| Vertical Boom Travel (Position 4 - Extender Mode)  | 41.25 in                       | 1.05 m   |
| Min. Camera Mt Height (Low Bar/Low 4-Way Leveling Head)  | 4.5 in                         | 11 cm    |
| Max. Camera Mt Height (Low Bar/Low 4-Way Leveling Head)  | 3 ft. 1 in.                    | 94 cm    |
| Chassis Width - All Legs at 0 degrees (Use in Tight Quarters)                                    | 20 in                          | 51 cm    |
| Chassis Width - All Legs at 10 degrees (Pneumatic or 880mm Pos)                                  | 25 in                          | 64 cm    |
| Chassis Width - All Legs at 45 degrees (Track Pos)   | 28 in                          | 71 cm    |
| Chassis Width - All Legs at 70 degrees (Tread & Wheel Base Equal)                                | 32 in                          | 81 cm    |
| Chassis Width - All Legs at 84 degrees (Sideways or Scissor Pos)                                 | 32.75 in                       | 83 cm    |
| Chassis Width - Front Legs at 84 degrees /Rear at 0 degrees (3 Point Med Tire)                   | 32.75 in                       | 83 cm    |
| Chassis Width - Front Legs at 84 degrees /Rear at 10 degrees (3 Point Pneu)                      | 32.75 in                       | 83 cm    |
| Chassis Width - Front Legs at 180 degrees /Rear at 0 degrees (Med Tire)                          | 20 in                          | 51 cm    |
| Chassis Width - Front Legs at 170 degrees /Rear at 10 degrees (Compact Pneu)                     | 25 in                          | 64 cm    |
| Steering Post Height   | 35 in                          | 89 cm    |
| Minimum Chassis Length   | 2 ft. 10 in.                   | 87.6 cm  |
| Maximum Chassis Length   | 3 ft. 10 in.                   | 1.16 m   |
| **Maximum Payload with High Post Kit   | 1,100 lb                       | 499 kg   |
| Maximum Number of Lifts on a Single Charge   | 5 lifts                        |          |
| Accumulator Charging Time (Empty to Full)  | 60 sec                         |          |
| Operational Weight   | 329 lb                         | 149 kg   |
| Operational Weight with High Post Kit (No Payload)   | 386 lb                         | 175 kg   |
| Dolly Shipping Weight w/Crate  | 487 lb                         | 220.8 kg |
| Dolly Shipping Crate Dimensions  | L 46 in. X W 28 in. X H 34 in. |          |
| Dolly Accessory Cart Shipping Weight w/Cart  | 854 lb                         | 387.3 kg |
| Dolly Accessory Cart Crate Shipping Dimensions   | L 55 in. X W27 in. XH 41 in.   |          |
| *Payload includes All items (i.e. Man, Camera, Platfor, Turret, Crane Arm, etc.) on Arm          |                                |          |
| **Payload includes All items (i.e. Man, Camera, Platform, Turret, Crane Arm, etc.) on Base Mount |                                |          |

**Accessories:**

- Medium Tire Set**
- 4-way leveling head**
- 12" Seat Riser (long post)**
- Seat offset arm (long post)**
- Universal low plate, tracking bars**
- Tracking bar 12" extension bars**
- Standing board**
- Full sideboards**
- sideboards**
- Upper & lower support boards**
- Full Filler plate**
- quarter filler plate**
- Star plate**
- Rear extension boards**
- upper & lower front boards**
- MI Boards**
- Lifting bars**
- Accessory cart & cover**
- 12" camera riser**
- 16" camera offset**
- 24" camera offset,**