

Profoto Pro-8a Air

Profoto Pro-8a 2400 Air

| | |
|----------------------|--|
| Energy | 2400 Ws |
| Energy control | 5 – 2400 Ws over an 10 f-stop range, in 1/10 or 1/1 increments. |
| Energy distribution | Fully asymmetric |
| Energy precision | ± 1/50 f-stop flash-to-flash |
| Color stability | ± 50° K over energy range 5.0 – 10.0 ± 40° K flash-to-flash |
| Recycling | 0.05 – 0.9 s |
| Lamp head connectors | Two connectors |
| Flash duration | 1/12,000 – 1/1600 s |
| Flash capacity | Up to 20 flashes per second |
| Modeling light | Up to 1000 W (max 500 W per head) |
| Size | 37 x 18.5 x 25 cm 14.5 x 7.3 x 9.8 inch |
| Weight | 12.2 kg 26.9 lbs |
| Input power supply | Multivoltage |
| Flash triggering | Built-in wireless Profoto Air with a range up to 300 m Built-in photocell, two sync sockets |
| Optional | Built-in LPA Pocket Wizard triggering system |
| Art. no. | 90 10 02 |

Profoto Pro-8a 1200 Air

| | |
|----------------------|--|
| Energy | 1200 Ws |
| Energy control | 5 – 1200 Ws over an 9 f-stop range, in 1/10 or 1/1 step increments. |
| Energy distribution | Fully asymmetric |
| Energy precision | ± 1/50 f-stop flash-to-flash |
| Recycling | 0.05 – 0.5 s |
| Color stability | ± 50° K over energy range 5.0 – 10.0 ± 40° K flash-to-flash |
| Lamp head connectors | Two connectors |
| Flash duration | 1/12,000 – 1/1600 s |
| Flash capacity | Up to 20 flashes per second |
| Modeling light | Up to 1000 W (max 500 W per head) |
| Size | 24.5 x 18.5 x 25 cm 13.6 x 7.3 x 9.8 inch |
| Weight | 11.4 kg 25.2 lbs |
| Input power supply | Multivoltage |
| Flash triggering | Built-in wireless Profoto Air with a range up to 300 m Built-in photocell, two sync sockets |
| Optional | Built-in LPA Pocket Wizard triggering system |
| Art. no. | 90 10 01 |