**TECHNOLOGY FOR FILM, TELEVISION, THEATRE AND EVENTS** 

## Ultratec LSG MKII

## Description

When you need to produce a dramatic and powerful fog effect, the Ultratec LSG MKII is "The Real Thing". When used with an Ultratec Fog Machine, the LSG MKII's patented CO2 conditioning process produces a huge, continuous output of low-lying fog. The LSG MKII can achieve many impressive effects including fog curtains and waterfall effects.

## Features:

- · Huge, Continuous Output
- · Remote, Show Control and DMX Control Available
- · Compact, Rugged Design
- Dry, White, Water-Based Effect
- · Proven Performance
- Patented CO2 Conditioning Process
- Industry Standard 3/4" CGA CO2 Fitting
- 110 volt
- · Optional Cart or Road Case
- · Optional Hanging Brackets Available
- · Available in two models:
  - o High Power Low Pressure CO2 (Independent solenoid and fan control)
  - o Low Pressure CO2 Dewar Delivery

Manufacturer	Ultratec
Effect Type	Low-Lying Fog
Required Material	CO2
Run Time	Continuous
Reheat Time	Continuous
CO2 Consumption	~15 lbs/minute (High Power), ~7.5 lbs/minute (Low Pressure)
Model Number	CLF 3962 (High Power), CLF 3950 (Low Pressure)
Weight (lbs)	100
Dimensions	25 x 19 x 23"